


## THE COMPLETE CABLE MANAGEMENT SUPPORT SYSTEM



The range consists of two pre-determined lengths of wire to support basket and tray. Safe Working Load:

- S 50kg
- G 10kg (on request)

Available in drops to suit basket or tray measuring:

- 50-200mm width
- 300-400mm width


The system is designed to be used in conjunction with Rize, Zip-Lock, Con-Lock, Dec-Lock, Shot-Lock & Uni-Lock.

- Reduces the use of studding and channel
- One fixing point per drop
- Allows for side loading
- Height can be adjusted at basket and not at fixing
- Can be fixed to basket at ground level

## APPLICATION

Suitable for suspending containment and bracketry:

- Cable Basket
- Cable Tray
- Channel Supports
- Chilled Beams
- Radiant Heat Panels



- ⇨ Plastic protection sleeve preventing wire on wire friction
- ⇨ High tensile galvanised wire 1960 N/mm<sup>2</sup> grade 7x7 construction
- ⇨ BSEN 12385 Standard
- ⇨ 5 x 50cm BZP Carabine Hook
- ⇨ Eyelets prevent accidental un-hooking of carabine from wire
- ⇨ Also available in stainless steel

## 50kg SWL

PRODUCT CODE	DESCRIPTION	SAFE WORKING LOAD
TRS50-200	300mm Try-Lock Support System. 10 Pieces per pack	50kg SWL
TRS300-400	460mm Try-Lock Support System. 10 Pieces per Pack	50kg SWL

### INSTALLATION METHOD

- The attachment of the Try-Lock system can be done at ground level
- Clip the carabine to one side of the Basket or cable tray
- Clip the other carabine to the other side of the basket or cable tray
- Pass the free end of the wire from your top suspension through the plastic protected loop and adjust the height and level required using the clip
- Legs should not exceed 60 degrees at the point of crimp.

