

UNI-LOCK

COMPLETE UNIVERSAL SYSTEM FOR PLUG AND SCREW APPLICATIONS



The range consists of a pre-determined length of wire from 1 metre to 10 metres with a choice of Safe Working Loads:

- G 10kg (Gas Nail/Screw)
- S 35kg (Screw only)

The system consists of wire and clip with a ferruled Uni-Lock bracket.

- Key free release system
- Suitable for both plug and screw and shot fire applications
- Tear drop shape allows for wire to rotate through 180° in bracket for angled applications
- Wire rotation reduces pressure on nail when service is not directly below anchor point


APPLICATION

Suitable for:

- Concrete Slab
- Metal Decking & other steel structures
- Wooden structures



- ◇ Plastic protection sleeve
- ◇ Trivalent zinc and clear galvanised bracket
- ◇ High tensile galvanised wire 1960 N/mm² grade 7x7 construction
- ◇ BSEN 12385 Standard



10kg SWL (Gas Nail/Screw)

PRODUCT CODE	DESCRIPTION	SAFE WORKING LOAD
ULG1	1 Metre Universal Bracket G	10kg SWL
ULG1.5	1.5 Metre Universal Bracket G	10kg SWL
ULG2	2 Metre Universal Bracket G	10kg SWL
ULG3	3 Metre Universal Bracket G	10kg SWL
ULG4	4 Metre Universal Bracket G	10kg SWL
ULG5	5 Metre Universal Bracket G	10kg SWL
ULG10	10 Metre Universal Bracket G	10kg SWL

INSTALLATION METHOD

- For timber applications pre-drill timber and use a screw to fix through the bracket
- For steel and concrete applications use self tapping fixing or a Gas nailer with a suitable nail.

35kg SWL (Screw only)

PRODUCT CODE	DESCRIPTION	SAFE WORKING LOAD
ULS1	1 Metre Universal Bracket S	35kg SWL
ULS1.5	1.5 Metre Universal Bracket S	35kg SWL
ULS2	2 Metre Universal Bracket S	35kg SWL
ULS3	3 Metre Universal Bracket S	35kg SWL
ULS4	4 Metre Universal Bracket S	35kg SWL
ULS5	5 Metre Universal Bracket S	35kg SWL
ULS10	10 Metre Universal Bracket S	35kg SWL

Sizes 6-9 metres are also available

